


TONA

1042B-L4106K-02

Solar Wall Bracket TONA Asymmetric IP44 LED SMD 6W 600lm CRI80
3000K Motion, Twilight Black

Dopo Lighting introduces the family solar wall lamps TONA. Manufactured with ABS and opalized polycarbonate. They have LED SMD technology. Your load time is 8 hours. 50lux sensor level. The colour temperature is 3000K and has a movement sensor allowing to select between three different modes of operation. It is designed to illuminate any type of residential exterior space without the need for electrical wiring. It is presented in symmetric and asymmetric version.



GENERAL DATA

Category	Surface
Family	Tona
Finish	[02] Black
Location	Outdoor
Installation	Wall
Body material	ABS
Diffuser material	Opal polycarbonate
ETIM class	EC0028g2
EAN	8433264353124

LIGHT SOURCES AND BEAMS

Sources	LED SMD 6W 600lm 3000K CRI80
Beam	Direct symmetric

TECHNICAL DATA

Dimensions	Length x Depth x Height (mm): 200 x 68 x 110
IP	IP44
Protection class	Class III
Input voltage	6V DC V
Sensors	Motion, Twilight
Rechargeable	Solar
Battery charge time	8.0 h
Battery output voltage	3.7 V
Operating temperature range	-10 - 40 °C
Power switches	1
Lifetime	30,000 h
LED lifetime L	80
LED lifetime B	50
Weight	0.4 Kg
Flammable surfaces	Yes

NOTES

Loading time: 8h
Duración carga completa: según cuadro adjunto
Nivel sensor: 50lux

TONA

1042B-L4106K-02 Solar Wall Bracket TONA Asymmetric IP44 LED SMD 6W 600lm CRI80
3000K Motion, Twilight Black

COMPLEMENTARY IMAGES

	MODE A	75lm	75lm	16h	
< 50 lux	MODE B	75lm	400lm x25seg	10h	
	MODE C	OFF	600lm x25seg	3h (ON+430)	

Tiempo de carga: 8h
Loading time: 8h
Temps de chargement: 8h



PRODUCTS OF THE SAME FAMILY



Tona