

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Glace

VK/04712/WA/D/TR/W

Transparent. 3000K. 5W. 195lm. AC220-240V. 120°. LED SMD2835.
Driver Eaglerise. Wall. -20°C → 60°C. 50.000hrs. Dimmable Yes, triac.
CRI>80. Aluminum + glass. IP20




IP20



Dimensions



Gallery





Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	5W
Voltage	AC220-240V
Fitting	Wall
Type	Light
Safety class	
Light source	SMD 2835
IP Rating	IP20
CRI	CRI>80
Dimmable	 TRIAC
Lifetime	50.000hrs
Clicks	20,000
Driver	Eaglerise
Working temperature	-20°C-60°C
PAGE	202 New Products 2026
NICKNAME	Glace

Physical Specifications	
Family	Glace
Color	Transparent
Material	Aluminum + glass
Width	ø13.5cm
Length	ø13.5cm
Height	8.5cm
Net weight of product (kg)	1.5kg
Gross weight with inner box (kg)	2kg
Width (inner box)	20cm
Length (inner box)	20cm
Height (inner box)	15cm

Illumination Data

Lumen	195lm
Beam angle	120°
Lighting direction	


Packing Info

Pcs/carton	4pcs
------------	------

Certification & Warranty

Guarantee	2 years
-----------	---------


Energy Label



VK LEADING LIGHT
VK/04712/WA/D/TR/W

A	▶
B	▶
C	▶
D	▶
E	▶
F	▶
G	▶

5 kWh/1000h



2019/2015