

SINCE 1978



LEADING LIGHT

# Product Datasheet

vkleadinglight.gr

Mim

## VK/04716/BS/W/60


Brass. 3000K. 1W. 74lm. DC24V. LED Bridgelux. 50.000hrs. Diffuse Light.  
Dimmable No. -20°C → 45°C. Outdoor ground. Included Spike & base.  
CRI>90. 60cm. Aluminum + Acrylic. IP65




IP65



### Dimensions



### Gallery




### Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	1W
Voltage	DC24V
Fitting	Outdoor ground
Type	Light
Safety class	N3
Light source	Bridgelux
IP Rating	<b>IP65</b>
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	-20°C-45°C
PAGE	378 New Products 2026
NICKNAME	Mim

Physical Specifications	
Family	Mim
Color	Brass
Material	Aluminum + acrylic
Width	ø2.5cm
Length	ø2.5cm
Height	60cm (+21cm of spike)

Illumination Data	
Lumen	74lm
Beam angle	Diffuse light
Lighting direction	

Packing Info	
Pcs/carton	30pcs

Certification & Warranty

Guarantee	3 years
-----------	---------

Energy Label

**ENERG**

VK LEADING LIGHT  
VK/04716/BS/W/60

A  
B  
C  
D  
E  
**F**  
G

1 kWh/1000h

2019/2015