



NIX 780A-G42X1B-45

Recessed ceiling NIX GU10 50W Chrome matt

NIX is a family of recessed LED discreet interior spaces that has been made from many applications and in two versions, one fixed and one steerable. NIX has been developed from two designs, one square and circular aluminum construction make it a functional and efficient luminaire for LED Indoor lighting.



GENERAL DATA

Category	Recessed
Family	Nix
Finish	[45] Chrome matt
Location	Indoor
Installation	Ceilling
Body material	Aluminum
Frame material	Aluminum
ETIM class	EC001744
EAN	8433264089030

LIGHT SOURCES AND BEAMS

Sources	GU10 QPAR-16 50W max.
Lamp included	No
Beam	Direct symmetric

TECHNICAL DATA

Dimensions	Height x Width x Length (mm): 78 x 78 x 55
IP	IP20
Protection class	Class II
Frequency	50/60 Hz
Input voltage	110-240V AC V
Auxiliary gear	Without equipment, not needed
Weight	0.055 Kg
Cut hole dimensions	Diameter (mm): 65
ECORAE category I	CAT-A

NIX 780A-G42X1B-45

Recessed ceiling NIX GU10 50W Chrome matt

RECOMMENDED ACCESSORIES

		B02T-X3360D-02 Power supplies ACCESORIOS Black	<table><tr><td>Input voltage</td><td>220-240V AC</td></tr><tr><td>Frequency</td><td>50/60</td></tr><tr><td>Wattage (W)</td><td>60.0</td></tr><tr><td>IP</td><td>IP20</td></tr></table>	Input voltage	220-240V AC	Frequency	50/60	Wattage (W)	60.0	IP	IP20			
Input voltage	220-240V AC													
Frequency	50/60													
Wattage (W)	60.0													
IP	IP20													
		B02T-X3370D-02 Power supplies ACCESORIOS Black	<table><tr><td>Input voltage</td><td>220-240V AC</td></tr><tr><td>Frequency</td><td>50/60</td></tr><tr><td>Wattage (W)</td><td>50.0</td></tr><tr><td>IP</td><td>IP20</td></tr></table>	Input voltage	220-240V AC	Frequency	50/60	Wattage (W)	50.0	IP	IP20			
Input voltage	220-240V AC													
Frequency	50/60													
Wattage (W)	50.0													
IP	IP20													
	578A-L2105A-02 Lamp LED PRO GU10 LED Bulb 4.50W 300lm CRI80 4000K 38° White	<table><tr><td>Input voltage</td><td>110-240V AC</td></tr><tr><td>Frequency</td><td>50/60</td></tr><tr><td>Wattage (W)</td><td>4.5</td></tr><tr><td>IP</td><td>IP20</td></tr><tr><td>Protection class</td><td>Class I</td></tr></table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	4.5	IP	IP20	Protection class	Class I		
Input voltage	110-240V AC													
Frequency	50/60													
Wattage (W)	4.5													
IP	IP20													
Protection class	Class I													
	578A-L2104A-01 Lamp LED PRO GU10 3,50W 36° White	<table><tr><td>Input voltage</td><td>110-240V AC</td></tr><tr><td>Frequency</td><td>50/60</td></tr><tr><td>Wattage (W)</td><td>3.5</td></tr><tr><td>IP</td><td>IP20</td></tr><tr><td>Protection class</td><td>Class I</td></tr></table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	3.5	IP	IP20	Protection class	Class I		
Input voltage	110-240V AC													
Frequency	50/60													
Wattage (W)	3.5													
IP	IP20													
Protection class	Class I													
	729A-L33R1B-00 Recessed ceiling ACCESORIOS 1-10V,Push LED COB 8W 803lm CRI85 4000K 40°	<table><tr><td>Input voltage</td><td>110-240V AC</td></tr><tr><td>Frequency</td><td>50/60</td></tr><tr><td>Wattage (W)</td><td>8.0</td></tr><tr><td>IP</td><td>IP20</td></tr><tr><td>Protection class</td><td>Class II</td></tr><tr><td>Dimmable</td><td>1-10V, Push</td></tr></table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	8.0	IP	IP20	Protection class	Class II	Dimmable	1-10V, Push
Input voltage	110-240V AC													
Frequency	50/60													
Wattage (W)	8.0													
IP	IP20													
Protection class	Class II													
Dimmable	1-10V, Push													
	578A-L2104A-02 Lamp LED PRO GU10 3,50W 36° White	<table><tr><td>Input voltage</td><td>110-240V AC</td></tr><tr><td>Frequency</td><td>50/60</td></tr><tr><td>IP</td><td>IP20</td></tr><tr><td>Protection class</td><td>Class I</td></tr></table>	Input voltage	110-240V AC	Frequency	50/60	IP	IP20	Protection class	Class I				
Input voltage	110-240V AC													
Frequency	50/60													
IP	IP20													
Protection class	Class I													
	729A-L31R1B-00 Recessed ceiling ACCESORIOS 1-10V,Push LED COB 8W 766lm CRI85 3000K 40°	<table><tr><td>Input voltage</td><td>110-240V AC</td></tr><tr><td>Frequency</td><td>50/60</td></tr><tr><td>Wattage (W)</td><td>8.0</td></tr><tr><td>IP</td><td>IP20</td></tr><tr><td>Protection class</td><td>Class II</td></tr><tr><td>Dimmable</td><td>1-10V, Push</td></tr></table>	Input voltage	110-240V AC	Frequency	50/60	Wattage (W)	8.0	IP	IP20	Protection class	Class II	Dimmable	1-10V, Push
Input voltage	110-240V AC													
Frequency	50/60													
Wattage (W)	8.0													
IP	IP20													
Protection class	Class II													
Dimmable	1-10V, Push													

NIX 780A-G42X1B-45

Recessed ceiling NIX GU10 50W Chrome matt



729A-L3108B-00

Recessed ceiling ACCESORIOS
LED COB 8W 766lm CRI85 3000K
40°

Input voltage	220-240V AC
Frequency	50/60
Wattage (W)	8.0
IP	IP20
Protection class	Class II



729A-L3308B-00

Recessed ceiling ACCESORIOS
LED COB 8W 803lm CRI85 4000K
40°

Input voltage	220-240V AC
Frequency	50/60
Wattage (W)	8.0
IP	IP20
Protection class	Class II

NIX 780A-G42X1B-45

Recessed ceiling NIX GU10 50W Chrome matt

PRODUCTS OF THE SAME FAMILY



Nix Round 2



Nix Round LED



Nix Round Tilt



Nix Round Tilt 2

Nix Round Tilt LED



Nix Square



Nix Square 2



Nix Square LED



Nix Square Tilt



Nix Square Tilt 2



Nix Square Tilt LED