




PROJECT
TYPE
NOTES
QUANTITY
DATE


Cone shaped ceiling suspended luminaire made from aluminium; surface Cement Grey + White Matt wet painted; matt texture; RAL 7033; inclusive black adjustable cable suspension max. 4000mm; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K colour warm dimming; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; ceiling base not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;


GENERAL

Ceiling
Suspended
Cement Grey + White Matt
RAL 7033 ^a
IP20
Interior
570 lm
CIE flux code: 81 94 99 100
100

LIGHT DISTRIBUTION

LED

colour warm dimming
1800 K - 2850 K
CRI ≥ 90
L80 / 60000h
initial MacAdam ≤ 3 SDCM

ELECTRICAL

phase-cut dim
220 - 240 V
system 12.0 W
Class 2

PHYSICAL

diameter 380 mm
height 460 mm
0.9 kg
cable length 4000 mm

^a Colour may deviate slightly due to production conditions.


Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMFa	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMFa	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES
Invisible ceiling base

Type	Colour	Voltage	L·W (MM)	Item number
	Black		140·66	90015195
	White		140·66	90015196

Semi recessed base

Type	Colour	Voltage	Ø·H (MM)	Item number
for shades without steel wire only	White		84·72	90052026
for shades without steel wire only	Black		84·72	90052027

Single base

Type	Colour	Voltage	Ø·H (MM)	Item number
ceiling base round	Black		84·29	90052021
ceiling base round	White		84·29	90052022