

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr


VK/04614/W-CB/W

Alo

Led Downlights waterproof, 3000K. 2.918lm. 25W. 95°. CRI>90, IP54, ø16.3x7.45cm, white+chrome+black



IP54    

Dimensions	Gallery	Downloads
		

Technical Specifications	
Kelvin	3000K
Power	25W
Voltage	220-240V
Fitting	Recessed ceiling
Type	Downlight LED
Safety class	
Light source	Bridgelux
IP Rating	IP54
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	<45°C
PAGE	246 Technical 2024
NICKNAME	Alo

Physical Specifications	
Recessed ceiling	Yes
Color	White+chrome+black
Material	Aluminium, PC reflector
Width	ø16.3cm
Length	ø16.3cm
Height	7.45cm
Net weight of product (kg)	0.57
Gross weight with inner box (kg)	0.71
Gross weight with master box (kg)	9.1
Cut out	ø15cm
Width (inner box)	19cm
Length (inner box)	23cm
Height (inner box)	9.5cm

Certification & Warranty	
Guarantee	5 years

Energy Label

ENERGY

VK LEADING LIGHT

VK 04614 W-CB/W

A

B

C

D

E

F

G

25 kWh/1000h

2019/2015